

## C H A S S I S   S P E C I F I C A T I O N S

	Description	Weight Front	Weight Rear	Retail Price
<b>Price Level</b>				
	M2 PRL-24M (EFF:01/19/21)			N/C
<b>Data Version</b>				
	SPECPRO21 DATA RELEASE VER 048			N/C
<b>Interior Convenience/Driver Retention Package</b>				
	INTERIOR CONVENIENCE PACKAGE WITH CB PROVISION			
<b>Vehicle Configuration</b>				
N	M2 106 CONVENTIONAL CHASSIS	5,709	3,503	
	2022 MODEL YEAR SPECIFIED			N/C
	SET BACK AXLE - TRUCK			STD
	TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK	10	10	
	LH PRIMARY STEERING LOCATION			STD
<b>General Service</b>				
	TRUCK/TRAILER CONFIGURATION			N/C
	DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)			STD
	PICKUP AND DELIVERY/SHORT HAUL SERVICE			STD
	GENERAL FREIGHT BUSINESS SEGMENT			STD
	GENERAL FREIGHT COMMODITY			STD
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS			STD
	MAXIMUM 8% EXPECTED GRADE			STD
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE			STD
	MEDIUM TRUCK WARRANTY			STD
	EXPECTED FRONT AXLE(S) LOAD : 12000.0 lbs			
	EXPECTED REAR DRIVE AXLE(S) LOAD : 21000.0 lbs			
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 33000.0 lbs			
	EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs			
<b>Truck Service</b>				

Description	Weight Front	Weight Rear	Retail Price
FLATBED/PLATFORM/STAKE BODY			N/C
WA JONES AND SON			N/C
EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0 in			
<b>Tractor Service</b>			
FLATBED TRAILER			N/C
SINGLE (1) TRAILER			N/C
<b>Engine</b>			
CUM L9 360 HP @ 2200 RPM; 2200 GOV RPM, 1150 LB-FT @ 1200 RPM	640	30	
<b>Electronic Parameters</b>			
75 MPH ROAD SPEED LIMIT			N/C
CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT			N/C
* NO FLEET SPEC FOR PARAMETERIZATION			N/C
REGEN INHIBIT SPEED THRESHOLD - 5 MPH			N/C
<b>Engine Equipment</b>			
2010 EPA/CARB/GHG21 CONFIGURATION			STD
2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)			
STANDARD OIL PAN			STD
ENGINE MOUNTED OIL CHECK AND FILL			STD
SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER			STD
DR 12V 200 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE			
(2) DTNA GENUINE, FLOODED STARTING, MIN 2000CCA, 370RC, THREADED STUD BATTERIES	10		
BATTERY BOX FRAME MOUNTED			STD
STANDARD BATTERY JUMPERS			STD
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB			STD
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN			STD
NON-POLISHED BATTERY BOX COVER			STD
CAB AUXILIARY POWER CABLE	5		N/C
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	10		
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2		
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE			STD
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR			STD
AIR COMPRESSOR DISCHARGE LINE			STD
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM			STD
C-BRAKE BY JACOBS WITH HIGH MED LOW BRAKE WITH BRAKE LAMPS	80		
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE			STD

	Description	Weight Front	Weight Rear	Retail Price
	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH			N/C
	STANDARD EXHAUST SYSTEM LENGTH			STD
	RH STANDARD HORIZONTAL TAILPIPE			STD
	13 GALLON DIESEL EXHAUST FLUID TANK	35	10	
	100 PERCENT DIESEL EXHAUST FLUID FILL			
	POLISHED ALUMINUM DIAMOND PLATE DIESEL EXHAUST FLUID TANK COVER	15	5	
	LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION			STD
	STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING			STD
	STANDARD DIESEL EXHAUST FLUID TANK CAP			STD
N	BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH			N/C
	AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED			STD
	CUMMINS SPIN ON FUEL FILTER			STD
	COMBINATION FULL FLOW/BYPASS OIL FILTER			N/C
	1100 SQUARE INCH ALUMINUM RADIATOR	70		N/C
	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT			STD
	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			STD
	GATES POWERGRIP SHRINK BAND HOSE CLAMPS WHERE POSSIBLE			
	RADIATOR DRAIN VALVE			STD
	LOWER RADIATOR GUARD			STD
	PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4		
	CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR			
	ALUMINUM FLYWHEEL HOUSING			
	ELECTRIC GRID AIR INTAKE WARMER			
	DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH			

### Transmission

	ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	200	60	
--	--	-----	----	--

### Transmission Equipment

	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV			N/C
	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES			N/C
	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			N/C
	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			N/C
	PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			STD

	Description	Weight Front	Weight Rear	Retail Price
	SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			STD
	PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			STD
	SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			STD
	ENGINE BRAKE RANGE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			STD
	ENGINE BRAKE RANGE ALTERNATE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			STD
	FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED			STD
	DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES			STD
	VEHICLE INTERFACE WIRING CONNECTOR WITH PDM AND NO BLUNT CUTS, AT BACK OF CAB			
	ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR FIREWALL MOUNTED			
	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN			STD
	PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED			N/C
	TRANSMISSION PROGNOSTICS - ENABLED 2013			N/C
	WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK			STD
	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK			N/C
	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)			STD

### Front Axle and Equipment

N	DETROIT DA-F-10.0-3 10,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE			N/C
	MERITOR EX+LS AXIAL AIR DISC FRONT BRAKES			
	NON-ASBESTOS FRONT BRAKE LINING			STD
	FRONT DISC BRAKE ROTORS			N/C
	FRONT OIL SEALS			STD
	VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL			STD
	STANDARD SPINDLE NUTS FOR ALL AXLES			STD
	FRONT AIR DISC BRAKE INTERNAL ADJUSTERS			N/C
	TRW THP-60 POWER STEERING			STD
	POWER STEERING PUMP			STD
	2 QUART SEE THROUGH POWER STEERING RESERVOIR			STD
	MINERAL SAE 80/90 FRONT AXLE LUBE			STD

### Front Suspension

N	10,000# TAPERLEAF FRONT SUSPENSION			
	MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION			STD
	FRONT SHOCK ABSORBERS			STD

Description	Weight Front	Weight Rear	Retail Price
<b>Rear Axle and Equipment</b>			
DETROIT DA-RS-23.0-4 23,000# R-SERIES SINGLE REAR AXLE		30	
3.08 REAR AXLE RATIO			N/C
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING			STD
SPL170 XL DANA SPICER MAIN DRIVELINE WITH HALF ROUND YOKES	5	5	
DRIVER CONTROLLED TRACTION DIFFERENTIAL - SINGLE REAR AXLE		20	
(1) DRIVER CONTROLLED DIFFERENTIAL LOCK REAR VALVE FOR SINGLE DRIVE AXLE			N/C
BUZZER AND BLINKING LAMP WITH EACH MODE SWITCH, DIFFERENTIAL UNLOCK WITH IGNITION OFF, ACTIVE <5 MPH			
MERITOR EX+LS AXIAL AIR DISC REAR BRAKES		-25	
NON-ASBESTOS REAR BRAKE LINING			STD
STANDARD BRAKE CHAMBER LOCATION			N/C
REAR DISC BRAKE ROTORS			N/C
REAR OIL SEALS			STD
AIR DISC LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS			N/C
REAR AIR DISC BRAKE INTERNAL ADJUSTERS			N/C
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE			STD
<b>Rear Suspension</b>			
AIRLINER 23,000# REAR SUSPENSION WITH CHAIN CLEARANCE		180	
AIRLINER HIGH POSITION RIDE HEIGHT			STD
STANDARD AXLE SEATS IN AXLE CLAMP GROUP			N/C
MANUAL DUMP VALVE FOR AIR SUSPENSION WITH GAUGE			
INDICATOR LIGHT AND BUZZER FOR EACH REAR SUSPENSION CONTROL SWITCH			
SINGLE AIR REAR SUSPENSION LEVELING VALVE			STD
TRANSVERSE CONTROL RODS			STD
REAR SHOCK ABSORBERS - ONE AXLE (AIR RIDE SUSPENSION)			STD
<b>Brake System</b>			
AIR BRAKE PACKAGE			STD
WABCO 4S/4M ABS			N/C
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES			STD
FIBER BRAID PARKING BRAKE HOSE			STD
STANDARD BRAKE SYSTEM VALVES			STD
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM			STD
STD U.S. FRONT BRAKE VALVE			STD
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE			STD
WABCO SYSTEM SAVER HP WITH INTEGRAL AIR GOVERNOR AND HEATER			STD
AIR DRYER FRAME MOUNTED			STD
ALUMINUM AIR BRAKE RESERVOIRS	-5	-5	

Description	Weight Front	Weight Rear	Retail Price
PULL CABLES ON ALL AIR RESERVOIR(S)			
<b>Trailer Connections</b>			
AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND DUST COVERS			
(1) ADDITIONAL AIR SWITCH WITH PLUMBING TO END OF FRAME	5	5	
PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION			N/C
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME			N/C
UPGRADED CHASSIS MULTIPLEXING UNIT			N/C
UPGRADED BULKHEAD MULTIPLEXING UNIT			N/C
<b>Wheelbase &amp; Frame</b>			
5075MM (200 INCH) WHEELBASE			N/C
9/32X3-7/16X10-1/16 INCH STEEL FRAME (7.14MMX255.6MM/0.281X10.06 INCH) 120KSI	40	-10	
1600MM (63 INCH) REAR FRAME OVERHANG			STD
FRAME OVERHANG RANGE: 61 INCH TO 70 INCH			N/C
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 87.01 in			
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 84.01 in			
CALC'D FRAME LENGTH - OVERALL : 292.18 in			
CALCULATED FRAME SPACE LH SIDE : 71.76 in			N/C
CALCULATED FRAME SPACE RH SIDE : 42.95 in			N/C
SQUARE END OF FRAME			STD
FRONT CLOSING CROSSMEMBER			STD
STANDARD WEIGHT ENGINE CROSSMEMBER			STD
STANDARD CROSSMEMBER BACK OF TRANSMISSION			STD
STANDARD MIDSHIP #1 CROSSMEMBER(S)			STD
STANDARD REARMOST CROSSMEMBER			STD
HEAVY DUTY SUSPENSION CROSSMEMBER		30	N/C
<b>Chassis Equipment</b>			
THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30		
FRONT TOW HOOKS - FRAME MOUNTED	15		
BUMPER MOUNTING FOR SINGLE LICENSE PLATE			N/C
BETTS B-60NT PAINTED MUDFLAP BRACKETS WITH NO TAPE		25	
BLACK MUDFLAPS		15	
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS			STD
HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS			
<b>Fuel Tanks</b>			
60 GALLON/227 LITER RECTANGULAR ALUMINUM FUEL TANK - RH	90	20	
60 GALLON/227 LITER RECTANGULAR ALUMINUM FUEL TANK - LH	30		
RECTANGULAR FUEL TANK(S)			STD
PLAIN ALUMINUM/HYDRAULIC TANK(S) WITH PAINTED ZINC-PLATED STEEL BANDS			

	Description	Weight Front	Weight Rear	Retail Price
N	LH FUEL TANK MOUNTED FORWARD, RH FUEL TANK MOUNTED AFT	-35	35	N/C
	BLACK STEP FINISH			
	CHROME FUEL TANK CAP(S)			
	DAVCO 245 FUEL/WATER SEPARATOR WITH ESOC AND WATER IN FUEL SENSOR	5		
	EQUIFLO INBOARD FUEL SYSTEM			STD
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE			STD
<b>Tires</b>				
	MICHELIN X LINE ENERGY Z 275/80R22.5 16 PLY RADIAL FRONT TIRES	4		
	MICHELIN X MULTI D 275/80R22.5 14 PLY RADIAL REAR TIRES		56	
<b>Hubs</b>				
	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS			STD
	CONMET PRESET PLUS PREMIUM IRON REAR HUBS			STD
<b>Wheels</b>				
	F/L BEVEL LOGO 40620 22.5X8.25 10-HUB PILOT 5.72 INSET ALUMINUM DISC FRONT WHEELS	-46		
	F/L BEVEL LOGO 40620 22.5X8.25 10-HUB PILOT 5.72 INSET ALUMINUM DISC REAR WHEELS		-92	
	POLISHED BOTH SIDES FRONT WHEELS WITH ACCU-SHIELD FINISH			
	POLISHED OUTER (BOTH SIDES) REAR WHEELS WITH OUTER ONLY ACCU-SHIELD FINISH			
	FRONT WHEEL MOUNTING NUTS			STD
	REAR WHEEL MOUNTING NUTS			STD
	NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES			
<b>Cab Exterior</b>				
	154 INCH BBC HIGH-ROOF ALUMINUM CONVENTIONAL CREW CAB	430	250	
	AIR CAB MOUNTING			
	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE			
	2-1/2 INCH FENDER EXTENSIONS	10		
	LH AND RH EXTERIOR GRAB HANDLES WITH SINGLE RUBBER INSERT			
	HOOD MOUNTED CHROMED PLASTIC GRILLE			
	CHROME HOOD MOUNTED AIR INTAKE GRILLE			
	FIBERGLASS HOOD			STD
	CUSTOM NOISE SHIELD-ENG COMPARTMENT			
	DUAL 24 INCH ROUND POLISHED ALUMINUM AIR HORNS ROOF MOUNTED	8		
	DUAL ELECTRIC HORNS			
	DUAL HORN SHIELDS			N/C
	REAR LICENSE PLATE MOUNT END OF FRAME			STD
	INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL			N/C
	LED AERODYNAMIC MARKER LIGHTS			
	RECTANGULAR CLEAR FOG LIGHTS MOUNTED UNDER BUMPER	6		

Description	Weight Front	Weight Rear	Retail Price
FREIGHTLINER LED FLANGE MOUNTED STOP/TAIL/TURN LIGHTS WITH SEPARATE INCANDESCENT BACKUP LIGHTS		5	
STANDARD FRONT TURN SIGNAL LAMPS			STD
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LED LIGHTS AND LH AND RH REMOTE			
DOOR MOUNTED MIRRORS			STD
102 INCH EQUIPMENT WIDTH			STD
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS			N/C
STANDARD SIDE/REAR REFLECTORS			STD
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH POLISHED DIAMOND PLATE COVER			
AERO BRIGHT EXTERIOR SUN VISOR	10		
63X14 INCH TINTED REAR WINDOW			STD
TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS			
RH AND LH ELECTRIC POWERED WINDOWS, PASSENGER SWITCHES ON DOOR(S)	4	4	
1-PIECE SOLAR GREEN GLASS WINDSHIELD			STD
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED			STD

### Cab Interior

OPAL GRAY VINYL INTERIOR			N/C
MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR			
MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR			
BLACK MATS WITH SINGLE INSULATION			STD
DASH MOUNTED ASH TRAY(S) WITHOUT LIGHTER			
FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT NETTING			N/C
(1) STORAGE CONSOLE WITH WRITING SURFACE FLOOR MOUNTED BETWEEN DRIVER AND PASSENGER SEATS	30		
DIGITAL FLUSH MOUNTED ALARM CLOCK IN DASH			
(2) CUP HOLDERS LH AND RH DASH			STD
GRAY/CHARCOAL WING DASH			
SMART SWITCH EXPANSION MODULE			
2-1/2 LB. FIRE EXTINGUISHER	5		
HEATER, DEFROSTER AND AIR CONDITIONER			STD
STANDARD HVAC DUCTING			STD
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH			STD
STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES			
VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR			STD
BINARY CONTROL, R-134A			STD
PREMIUM INSULATION			



	Description	Weight Front	Weight Rear	Retail Price
	SOLID-STATE CIRCUIT PROTECTION AND FUSES			STD
	12V NEGATIVE GROUND ELECTRICAL SYSTEM			STD
	DOOR ACTIVATED DOME/RED MAP LIGHTS, FORWARD LH AND RH AND REAR LH, RH AND CENTER			N/C
	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME			STD
	KEY QUANTITY OF 4			
	LH AND RH ELECTRIC DOOR LOCKS			
	(1) 12V POWER SUPPLY (1) DUAL 2.1 AMP USB CHARGER IN DASH			
	TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB	10		
*	ELITE HIGH BACK AIR SUSPENSION DRIVER SEAT WITH HEAT, 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT AND ADJUSTABLE SHOCK			
*	ELITE HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH HEAT, 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT AND ADJUSTABLE SHOCK			
	FULL WIDTH REAR BENCH SEAT WITH FOLDING BACK	75	20	
N	INBOARD DRIVER AND PASSENGER SEAT ARMRESTS	4		
	LH AND RH INTEGRAL DOOR PANEL ARMRESTS			STD
N	BLACK LAREDO LEATHER DRIVER SEAT COVER			
N	BLACK LAREDO LEATHER PASSENGER SEAT COVER			
*	BLACK MORDURA CLOTH REAR PASSENGER SEAT COVER			
	BLACK SEAT BELTS WITH DRIVER INDICATOR LIGHT AND AUDIBLE ALARM			
	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	10		
	18 INCH (450MM) LEATHER WRAPPED STEERING WHEEL			
	DRIVER AND PASSENGER INTERIOR SUN VISORS			STD
	INTERFACE CONNECTORS AND WIRING FOR CUSTOMER PROVIDED LED STEP LIGHTING			
<b>Instruments &amp; Controls</b>				
	WOODGRAIN DRIVER INSTRUMENT PANEL			N/C
	WOODGRAIN CENTER INSTRUMENT PANEL			N/C
	BLACK GAUGE BEZELS			N/C
	LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM			STD
	(1) SINGLE BRAKE APPLICATION AIR GAUGE			
	2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES			N/C
	DASH MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS			
	ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B DASH PANEL)			

Description	Weight Front	Weight Rear	Retail Price
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY			STD
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED			N/C
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH			STD
2 INCH ELECTRIC FUEL GAUGE			STD
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE			STD
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE			N/C
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY			STD
ELECTRIC ENGINE OIL PRESSURE GAUGE			STD
OVERHEAD INSTRUMENT PANEL			STD
AM/FM/WB WORLD TUNER RADIO WITH SIRIUSXM, BLUETOOTH, IPOD INTERFACE, USB AND AUXILIARY INPUTS, J1939	10		
DASH MOUNTED RADIO			N/C
(2) RADIO SPEAKERS IN CAB			N/C
24 INCH AM/FM ANTENNA MOUNTED ON LH SIDE MIRROR, RG-62			
POWER AND GROUND WIRING PROVISION OVERHEAD			N/C
CB WIRING ONLY TO ROOF/OVERHEAD CONSOLE; NO MOUNTING PROVISION			N/C
INTEROPERABLE SDAR ANTENNA			
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER			STD
STANDARD VEHICLE SPEED SENSOR			STD
ELECTRONIC 3000 RPM TACHOMETER			STD
IDLE LIMITER, ELECTRONIC ENGINE			N/C
TWO ON/OFF ROCKER SWITCHES IN THE DASH WITH INDICATOR LIGHTS AND WIRE ROUTED TO CHASSIS AT BACK OF CAB, LABEL OPT			
BW TRACTOR PROTECTION VALVE			N/C
TRAILER HAND CONTROL BRAKE VALVE			N/C
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY			STD
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY			STD
MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH			N/C
TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR			N/C
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE			N/C
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS			STD
<b>Design</b>			
PAINT: ONE SOLID COLOR			STD
<b>Color</b>			
CAB COLOR A: N0006EA WHITE ELITE SS			N/C

Description	Weight Front	Weight Rear	Retail Price
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT			STD
STANDARD E COAT/UNDERCOATING			STD

### Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS			STD
---	--	--	-----

### Secondary Factory Options

NO TIRE INFLATION DEVICE/SYSTEM			STD
* OBD 2019 MISFIRE MONITORING			N/C
* VEHICLE IS SUBJECT TO EPA GHG21			N/C
* J1939 ELECTRICAL ARCHITECTURE			N/C
* 50 STATE EMISSIONS CERTIFICATION			N/C
* STANDARD DIESEL EXHAUST FLUID SYSTEM COOLANT PLUMBING			N/C
* DISABLE - NEUTRAL RANGE ASSIST			N/C
* AUXILIARY FUNCTION RANGE INHIBIT WITH MULTIPLEXED SERVICE BRAKES - ALLISON 5TH GEN TRANSMISSIONS			N/C
* SINGLE INPUT AUTOMATIC NEUTRAL WITH SELECTOR OVERRIDE WITH MULTIPLEXED PARK BRAKE - ALLISON 5TH GEN TRANSMISSIONS			N/C
* STEEL STEERING SHAFT			N/C
* STANDARD AIR MANAGEMENT UNIT			N/C

### Raw Performance Data

CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 84.01 in

### Sales Programs

N	BUSINESSQUOTE		N/C
---	---------------	--	-----

## TOTAL VEHICLE SUMMARY

### Adjusted List Price

Adjusted List Price \*\*

### Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	7540 lbs	4186 lbs	11726 lbs
Total Weight <sup>+</sup>	7540 lbs	4186 lbs	11726 lbs